

## Stoßverbinder

- Kupfer, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

| Art. Nr. | LQ      | A  | GL | kg/100 | VE      |
|----------|---------|----|----|--------|---------|
| 363500   | 0,5-1,0 | 14 | 36 | 0,120  | 500 100 |
| 363502   | 1,5-2,5 | 15 | 36 | 0,132  | 500 100 |
| 363504   | 4,0-6,0 | 15 | 41 | 0,300  | 500 100 |

## Flachsteckhülsen

- Messing, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

| Art. Nr. | LQ      | FSt.    | GL   | B   | B   | kg/100 | VE      |
|----------|---------|---------|------|-----|-----|--------|---------|
| 363510   | 0,5-1,0 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,129  | 500 100 |
| 363512   | 1,5-2,5 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,138  | 500 100 |
| 363514   | 4,0-6,0 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,200  | 500 100 |

## Flachstecker

- Messing, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

| Art. Nr. | LQ      | FSt.    | GL   | B   | B   | kg/100 | VE      |
|----------|---------|---------|------|-----|-----|--------|---------|
| 363520   | 0,5-1,0 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,092  | 500 100 |
| 363522   | 1,5-2,5 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,106  | 500 100 |
| 363524   | 4,0-6,0 | 6,3x0,8 | 30,0 | 6,6 | 6,6 | 0,159  | 500 100 |

## Ringkabelschuhe

- Kupfer, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

| Art. Nr. | LQ      | M  | d2   | GL   | B    | B    | kg/100 | VE      |
|----------|---------|----|------|------|------|------|--------|---------|
| 363530   | 0,5-1,0 | 4  | 4,3  | 28,5 | 8,0  | 8,0  | 0,073  | 500 100 |
| 363532   |         | 5  | 5,3  | 28,5 | 8,0  | 8,0  | 0,066  | 500 100 |
| 363534   |         | 6  | 6,5  | 34,5 | 11,6 | 11,6 | 0,104  | 500 100 |
| 363536   |         | 8  | 8,4  | 34,5 | 11,6 | 11,6 | 0,089  | 500 100 |
| 363538   |         | 10 | 10,5 | 37,5 | 13,6 | 13,6 | 0,112  | 500 100 |
| 363540   | 1,5-2,5 | 4  | 4,3  | 30,5 | 8,5  | 8,5  | 0,085  | 500 100 |
| 363542   |         | 5  | 5,3  | 30,5 | 9,5  | 9,5  | 0,083  | 500 100 |
| 363544   |         | 6  | 6,5  | 35,5 | 12,0 | 12,0 | 0,122  | 500 100 |
| 363546   |         | 8  | 8,4  | 35,5 | 12,0 | 12,0 | 0,118  | 500 100 |
| 363548   |         | 10 | 10,5 | 37,5 | 13,6 | 13,6 | 0,128  | 500 100 |
| 363550   | 4,0-6,0 | 4  | 4,3  | 34,2 | 9,5  | 9,5  | 0,173  | 500 100 |
| 363552   |         | 5  | 5,3  | 34,0 | 9,5  | 9,5  | 0,172  | 500 100 |
| 363554   |         | 6  | 6,5  | 37,5 | 12,0 | 12,0 | 0,201  | 500 100 |
| 363556   |         | 8  | 8,4  | 42,0 | 15,0 | 15,0 | 0,251  | 500 100 |
| 363558   |         | 10 | 10,5 | 42,0 | 15,0 | 15,0 | 0,226  | 500 100 |

## Löt-Schrumpfverbinder

- Kupfer, verzinkt • RoHS-konform • kein Presswerkzeug nötig
- Isolierhülle: Polyolefin mit Innenkleber

| Art. Nr. | LQ      | kg/100 | VE |
|----------|---------|--------|----|
| 363600   | 0,5-1,0 | 0,090  | 1  |
| 363602   | 1,5-2,5 | 0,110  | 1  |
| 363604   | 4,0-6,0 | 0,160  | 1  |

